



Gahar Lorestan
Petro refinery company

هیدروکربن سبک حاصل از برش دوم میعانات گازی پارس جنوبی دارای کد عمومی 111110132

Heavy End

QUALITY

TEST	METHOD	UNIT	GUARANTEE RANGE	
Sp.GR @ 60°F	ASTM D 4052	0.795	790-810	
Density		Kg/m³		
Distillation				
IBP	ASTM D 86	°C	133	129-177
5% recovered at	ASTM D 86	°C	147	143-186
10% recovered at	ASTM D 86	°C	154	149-192
20% recovered at	ASTM D 86	°C	163	158-204
30% recovered at	ASTM D 86	°C	173	168-217
40% recovered at	ASTM D 86	°C	183	178-226
50% recovered at	ASTM D 86	°C	194	191-235
60% recovered at	ASTM D 86	°C	208	205-245
70% recovered at	ASTM D 86	°C	227	220-256
80% recovered at	ASTM D 86	°C	249	239-282
90% recovered at	ASTM D 86	°C	284	267-297
95% recovered at	ASTM D 86	°C	318	291-319
FBP	ASTM D 86	°C	336	320-342
Recovery	ASTM D 86	Vol%	99	99-99.5
Lost	ASTM D 86	Vol%	0.5	0
Residue	ASTM D 86	Vol%	0.5	0.5
Flash Point(close)	ASTM D 93	15 °C	39	27-70
Total Sulphur	INSO 8402	ppm	3000	